

Specifications

Module	DM2.6
Pixel Pitch	2.60mm
Max. Brightness Calibrated	1,500nits
Panel Dimension	500 x 500 x 80mm 19.7" x 19.7" x 3.2"
Panel Resolution (H x V)	192 x 192
Weight per panel	5.76kg; 12.7lbs
Power Consumption Max/Average	180W / 90W
BTU Max/Average	614 / 282
Transparency	Solid
Max. Curving degree	Concave 10° - Convex 5°
Max. Hanging (panels)*1	20
Max. Stacking (panels)*2	10
LED Configuration	SMD 1515 Black
Viewing Angle Vertical	140°
Viewing Angle Horizontal	140°
Multiplexing	16
Refresh Rate	3840Hz
Gray Scale	16bit
Frame Material	Magnesium
Operational Temp / Humidity	-20°- 45°C, 10-90%RH -4°-113°F, 10-90%RH
Storage Temp / Humidity	-40°- 60°C, 10-90% RH / -40°-140°F, 10-90% RH
IP Rating (front/rear)	Indoor
Certifications	CE, ETL,TUV

*Notes: The Specifications are for reference, actual values may vary.

1. The max. hanging amount is only valid when the ROE Visual hanging bar and complementary accessories are used and in an indoor situation. No climbing is allowed.
2. The max. stacking amount is only valid when the ROE Visual stacking system and complementary accessories are used, sufficient ballast is applied and in an indoor situation. No climbing is allowed.

Dimensions



www.roevisual.com

ROE Visual Co., Ltd. | ROE Visual US, Inc. | ROE Visual Europe BV
 roe@roevisual.com | roe@roevisual.com | roe@roevisual.com