

Magic Cube



■ Features

Easy Installation


Magnets within the panels allow for easy assembly by one person.

Frame Compatibility

All Carbon, Magic Cube, and Hybrid panels share the same frame for the ability to easily mix and match.

Touring Option

Our innovative touring system provides a convenient all-in-one solution for packaging, transport, installation, and maintenance.



■ Specifications

| Magic Cube | MC-5H | MC-7H | MC-9H | MC-12H | MC-18H |
|--------------------------------------|--|--|--------------------------------------|--------------------------------------|--------------------------------------|
| Pixel Pitch | 5.769 mm | 7.5 mm | 9.375 mm | 12.5 mm | 18.75 mm |
| Pixel Density | 30,044/sqm | 17,778/sqm | 11,378/sqm | 6,400/sqm | 2,844/sqm |
| Pixel / Tile | 104×104 | 80×80 | 64×64 | 48×48 | 32×32 |
| LED Configuration | HB Black/White SMD 3-in-1 | HB Black/White SMD 3-in-1 | White SMD 3-in-1 | White SMD 3-in-1 | White SMD 3-in-1 |
| Max. Brightness | 5,000 nits (Multicolor 2727) 6,000 nits (NationStar 2727) | 5,000 nits (Multicolor 3535) 5,000 nits (NationStar 2727) | 5,500 nits (NationStar 3535) | 6,000 nits (NationStar 3535) | 4,800 nits (NationStar 3535) |
| Viewing Angle | 140°/120°(H/V) | 140°/120°(H/V) | 140°/120°(H/V) | 140°/120°(H/V) | 140°/120°(H/V) |
| Transparency | Solid | Solid | 17% | 21% | 37% |
| Tile Dimension (W×H×D)Light Frame | 600mm×600mm×89mm 23.6"×23.6"×3.5" | 600mm×600mm×85mm 23.6"×23.6"×3.3" | 600mm×600mm×85mm 23.6"×23.6"×3.3" | 600mm×600mm×85mm 23.6"×23.6"×3.3" | 600mm×600mm×85mm 23.6"×23.6"×3.3" |
| Tile Dimension (W×H×D)Tour Frame | 600mm×600mm×95mm 23.6"×23.6"×3.7" | 600mm×600mm×95mm 23.6"×23.6"×3.7" | 600mm×600mm×95mm 23.6"×23.6"×3.7" | 600mm×600mm×95mm 23.6"×23.6"×3.7" | 600mm×600mm×95mm 23.6"×23.6"×3.7" |
| Tile Weight (Light Frame) | / | 10.4kg 9.5kg | 8.0kg | 7.5kg | 7.0kg |
| Tile Weight (Touring Frame) | 17.0kg | 15.7kg/ 14.8kg | 13.3kg | 12.8kg/ | 12.2kg |
| Max. Hanging | 20 tiles | 20 tiles | 20 tiles | 20 tiles | 20 tiles |
| Max. Stacking (Touring Frame) | 8 tiles | 8 tiles | 8 tiles | 8 tiles | 8 tiles |
| IP Rating(Front/Rear) | IP65 | IP65 | IP65 | IP65 | IP65 |
| Curve | -10° / 0° / +10° | -10° / 0° / +10° | -10° / 0° / +10° | -10° / 0° / +10° | -10° / 0° / +10° |
| Gray Scale | 16bit | 16bit | 16bit | 16bit | 16bit |
| Scan | 1/4 | 1/5 | 1/4 | Static | Static |
| Refresh Rate | 3,840Hz | 2,000Hz | 3,500Hz | 4,000Hz | 4,000Hz |
| Max Power/Tile | 400W 280W | 420W 300W | 320W | 320W | 250W |
| Processor | Evision | Evision | Evision | Evision | Evision |
| Lifetime | ≥50,000h | ≥50,000h | ≥50,000h | ≥50,000h | ≥50,000h |
| Ope Temp/Hum | -20°C to 45°C, 10~90%RH | -20°C to 45°C, 10~90%RH | -20°C to 45°C, 10~90%RH | -20°C to 45°C, 10~90%RH | -20°C to 45°C, 10~90%RH |
| Sto Temp/Hum | -40°C to 60°C, 10~90%RH | -40°C to 60°C, 10~90%RH | -40°C to 60°C, 10~90%RH | -40°C to 60°C, 10~90%RH | -40°C to 60°C, 10~90%RH |
| Certifications | — | CE ETL TUV | CE ETL TUV | CE ETL TUV | CE ETL TUV |

■ Dimensions

